





















Price List

Item No.	Picture	Product name	Description & Features	RANTEX PRICE INCLUDING VAT
AC222401D-R		Diesel engine Air compressor	<p>Diesel engine,radiator cooling Belt driver compressor Air displacement(m³/min):4.0 Exhaust pressure(Mpa):0.5 Cylinder(Dia.×Qty):120°4 Diesel engine(HP):22 Tank capacity:240L Weight (kg):700 Pump lubricated with oil With Electric Start Packed by wood box</p>	5040.00
HHRD0221		Hand-hold rock drill	<p>Length:550mm Cylinder Dia.×Stroke: 58×45mm Air pressure:0.4- 0.63Mpa Shank Size:22*108mm Impact energy: ≥22J Impact frequency≥32HZ Air consumption≤20l/s Weight: 18Kgs Packed in carton box</p>	441.00
ALRD0651		Air Leg Rock Drill	<p>Air consumption: ≤65L/S Drilling Frequency: ≥37HZ Air pipe inner Diameter: 25MM Water pipe inner Diameter: 13MM Drilling Hole Diameter: 32-45MM Drilling Depth: 5M Shank Size:22*108mm Air pressure:0.4- 0.63Mpa Size:659*248*205mm Weight :26.5 KG Packed in carton box</p>	1260.00
ALA0020		Air leg	<p>Length: 1312MM Pushing stroke: 810MM Cylinder diameter: 52mm Weight: 11Kgs Packed by carton box Suitable for HHRD0221</p>	367.50
AH2201		Air Rubber Hose	<p>20M/roll Material: rubber Color: black Inside diameter: 25mm Outside Diameter: 36mm working pressure(Mpa): 1.5-2 Burst pressure(Mpa): 4.5-6 Packed in rolls Suitable for ALRD0651</p>	94.50
ATDR0101		Taper Drill Rods	<p>Taper: 7 degree Shank size: H22*108mm Length:1M Packed in Linen bag Suitable for ALRD0651</p>	20.48
ATDR0151		Taper Drill Rods	<p>Taper: 7 degree Shank size: H22*108mm Length:1.5M Packed in Linen bag Suitable for ALRD0651</p>	30.98
ATDR0201		Taper Drill Rods	<p>Taper: 7 degree Shank size: H22*108mm Length:2M Packed in Linen bag Suitable for ALRD0651</p>	41.48
ATDR0103		Taper Drill Rods- Long Shank	<p>Taper: 11 degree Shank size: H22*159mm Length:1M Packed in Linen bag MOQ:200pcs</p>	29.40
ATDR0153		Taper Drill Rods- Long Shank	<p>Taper: 11 degree Shank size: H22*159mm Length:1.5M Packed in Linen bag MOQ:200pcs</p>	43.05
DBC0321		Chisel Bit	<p>Bit Diameter: 32mm Buttons (mm) : 10*15 Taper: 7 degree Water Hole: 2 Packed in carton box Suitable for INGCO Taper Drill Rods</p>	19.95

DBSB0382		Button Bit	Bit Diameter: 38mm Buttons (mm) : Gauge: 3*8; Front: 1*8; Angle: 25° Taper: 7 degree Water Hole: 2 Packed in carton box Suitable for INGCO Taper Drill Rods	23.10
DBSB0383		Button Bit	Bit Diameter: 38mm Buttons (mm) : Gauge: 3*8; Front: 1*8; Angle: 25° Taper: 11 degree Water Hole: 2 Packed in carton box Suitable for INGCO Taper Drill Rods	23.10
AHC001		Connector	Hose connector Material:carton steel,heat treatment	9.98
AHC002		Connector	Hose connector Material:carton steel,heat treatment	12.60
AHC003		Connector	Hose connector Material:carton steel,heat treatment	9.98
AHC004		Connector	Hose connector Material:carton steel,heat treatment	9.98
CB050601		Conveyor Belt	Belt width (mm) : 500 Belt length (m) : 6 Motor Power (KW): 3 Conveying speed (m/s) : 1.3-1.6 Conveying amount (t/h) : 78-151 Copper wire Motor Packed in bulk	5040.00
DES11301N		Diesel Engine with radiator water cooled	4 stroke, horizontal Single cylinder, water cooled BorexStroke:130x120mm Displacement:1.593L Compression ratio:17:1 Max output:30HP Rated output:28HP No load speed:2200rpm Cooling system:Radiator Starting system:Hand cranking Combustion system:Direction Fuel tank:20L Fuel consumption:181g/Kw.H Continuous operation:3.5Hr Net weight:226Kgs	1349.25
DES1801		Diesel Engine with water cooled	4 stroke, horizontal Single cylinder, water cooled BorexStroke:80x80mm Displacement:0.402L Compression ratio:22:1 Max output:7.7HP Rated output:7HP No load speed:2600rpm Cooling system:Evaporative Starting system:Hand cranking Combustion system:Swirl Fuel tank:4L Fuel consumption:205g/Kw.H Continuous operation:2.8Hr Net weight:80Kgs Packed by carton box	467.25
ADP201		Air Diaphragm Pump	Size: 2" Center block material:Aluminum Wetted body material:Aluminum Diaphragm material:HYTREL Ball material:PC Seat material:HYTREL Max. Flow(l/min):587 Max. HEAD: 84m Max. pressure(bar):8.4 Max.grain diameter(mm):6 Dry suction(m):5 Packed by wood box	2100.00
MHF15001		Centrifugal pump	Voltage:220-240V~50Hz Input power: 1500W(2HP) Max.head:18M Max. suction:8M Max. flow:500L/min Pipe diameter:2"x2" Copper wire motor Copper impeller 0.15m length cable Packed by carton box	294.00
MHF22001		Centrifugal pump	Voltage:220-240V~50Hz Input power: 2200W(3HP) Max.head:15M Max. suction:8M Max. flow:800L/min Pipe diameter:3"x3" Copper wire motor Copper impeller 0.15m length cable Packed by carton box	378.00

SPM15001		Slurry pump	Rated voltage:380V Rated frequency:50HZ Phase:Three Rated power:1.5Kw(2HP) No load speed:2860rpm Max. flow: 22m3/h Max. head: 18m Suction head:8m Outlet:40mm Packed by wood box	546.00
SPM30001		Slurry pump	Rated voltage:380V Rated frequency:50HZ Phase:Three Rated power:3.0Kw(4HP) No load speed:2860rpm Max. flow: 30 m3/h Max. head: 20 m Suction head:8m Outlet:40mm Packed by wood box	729.75
SPM75001		Slurry pump	Rated voltage:380V Rated frequency:50HZ Phase:Three Rated power:7.5Kw(10HP) No load speed:2860rpm Max. flow: 120m3/h Max. head: 22 m Suction head:8m Outlet:40mm Packed by wood box	1942.50
EHJM0752		Electric hoists	Motor Power (KW): 4.0 Rated force of steel rope(KN):7.5(0.75T) Dimension of steel rope(mm):7.7 Rope capacity(m):200 Average rope speed(m/min):18 Weight (kg):168 Packed by wood box	2887.50
HDEPW0101.1		Water-cooled Diesel Engine Winch	Lifting Capacity:1 tonnes Diesel engine,4.0HP,radiator type Wire Rope size:Φ8MM×225M Engine Speed (rpm):2600 Rope speed: Low gear speed (m/min):5.4-7.5 High gear speed (m/min):9.7-13.4 High work duty cycle for continuous use Packed by wood box	5145.00
HC400600		Hammer crusher	Voltage:380V,50HZ,3PHASE Feed opening (mm): 400×600 Max feed size (mm): ≤50 Layout size (mm): ≥1.8 Capacity (t/h):1-3 Motor Power (KW): 22 Copper wire Motor Packed in steel box	12075.00
JC150250		Jaw Crusher	Feed opening (mm): 150X250 Max feed size (mm): 125 Discharging Size (mm) : 10-40 Capacity (t/h):1-3 Power (KW) : 5.5 Weight: 850Kgs Packed by bulk	5617.50
EMY80M1-2		Three phase asynchronous motor	Rated voltage:380V Rated frequency:50HZ Phase :Three Pole:Two Rated power:0.75Kw(1HP) No load speed:2830RPM Power factor:0.84 Work duty:S1 Protection class:IP44 Insulation class:B Copper wire motor Packed by carton box	115.50
EMY90S-2		Three phase asynchronous motor	Rated voltage:380V Rated frequency:50HZ Phase :Three Pole:Two Rated power:1.5Kw(2HP) No load speed:2840RPM Power factor:0.85 Work duty:S1 Protection class:IP44 Insulation class:B Copper wire motor Packed by carton box	157.50
EMY90L-2		Three phase asynchronous motor	Rated voltage:380V Rated frequency:50HZ Phase :Three Pole:Two Rated power:2.2Kw(3HP) No load speed:2840RPM Power factor:0.86 Work duty:S1 Protection class:IP44 Insulation class:B Copper wire motor Packed by carton box	189.00
EMY112M-2		Three phase asynchronous motor	Rated voltage:380V Rated frequency:50HZ Phase :Three Pole:Two Rated power:4.0Kw(5.5HP) No load speed:2890RPM Power factor:0.86 Work duty:S1 Protection class:IP44 Insulation class:B Copper wire motor Packed by wood box	309.75

EMY132S2-2		Three phase asynchronous motor	Rated voltage:380V Rated frequency:50HZ Phase :Three Pole:Two Rated power:7.5Kw(10HP) No load speed:2900RPM Power factor:0.88 Work duty:S1 Protection class:IP44 Insulation class:B Copper wire motor Packed by wood box	472.50
EMY160M1-2		Three phase asynchronous motor	Rated voltage:380V Rated frequency:50HZ Phase :Three Pole:Two Rated power:11.0Kw(15HP) No load speed:2930RPM Power factor:0.88 Work duty:S1 Protection class:IP44 Insulation class:B Copper wire motor Packed by wood box	787.50
EMY160M2-2		Three phase asynchronous motor	Rated voltage:380V Rated frequency:50HZ Phase :Three Pole:Two Rated power:15.0Kw(20HP) No load speed:2930RPM Power factor:0.88 Work duty:S1 Protection class:IP44 Insulation class:B Copper wire motor Packed by wood box	855.75
EMY160L-2		Three phase asynchronous motor	Rated voltage:380V Rated frequency:50HZ Phase :Three Pole:Two Rated power:18.5Kw(25HP) No load speed:2930RPM Power factor:0.89 Work duty:S1 Protection class:IP44 Insulation class:B Copper wire motor Packed by wood box	966.00
EMY180M-2		Three phase asynchronous motor	Rated voltage:380V Rated frequency:50HZ Phase :Three Pole:Two Rated power:22Kw(30HP) No load speed:2940RPM Power factor:0.89 Work duty:S1 Protection class:IP44 Insulation class:B Copper wire motor Packed by wood box	1286.25
EMY80M2-4		Three phase asynchronous motor	Rated voltage:380V Rated frequency:50HZ Phase :Three Pole:Four Rated power:0.75Kw(1HP) No load speed:1390RPM Power factor:0.76 Work duty:S1 Protection class:IP44 Insulation class:B Copper wire motor Packed by carton box	126.00
EMY90L-4		Three phase asynchronous motor	Rated voltage:380V Rated frequency:50HZ Phase :Three Pole:Four Rated power:1.5Kw(2HP) No load speed:1400RPM Power factor:0.79 Work duty:S1 Protection class:IP44 Insulation class:B Copper wire motor Packed by carton box	178.50
EMY100L1-4		Three phase asynchronous motor	Rated voltage:380V Rated frequency:50HZ Phase :Three Pole:Four Rated power:2.2Kw(3HP) No load speed:1430RPM Power factor:0.82 Work duty:S1 Protection class:IP44 Insulation class:B Copper wire motor Packed by carton box	236.25
EMY112M-4		Three phase asynchronous motor	Rated voltage:380V Rated frequency:50HZ Phase :Three Pole:Four Rated power:4.0Kw(5.5HP) No load speed:1430RPM Power factor:0.82 Work duty:S1 Protection class:IP44 Insulation class:B Copper wire motor Packed by wood box	320.25
EMY132M-4		Three phase asynchronous motor	Rated voltage:380V Rated frequency:50HZ Phase :Three Pole:Four Rated power:7.5Kw(10HP) No load speed:1400RPM Power factor:0.85 Work duty:S1 Protection class:IP44 Insulation class:B Copper wire motor Packed by wood box	546.00

EMY160M-4		Three phase asynchronous motor	Rated voltage:380V Rated frequency:50HZ Phase :Three Pole:Four Rated power:11.0Kw(15HP) No load speed:1460RPM Power factor:0.84 Work duty:S1 Protection class:IP44 Insulation class:B Copper wire motor Packed by wood box	782.25
EMY160L-4		Three phase asynchronous motor	Rated voltage:380V Rated frequency:50HZ Phase :Three Pole:Four Rated power:15.0Kw(20HP) No load speed:1460RPM Power factor:0.85 Work duty:S1 Protection class:IP44 Insulation class:B Copper wire motor Packed by wood box	955.50
EMY180ML-4		Three phase asynchronous motor	Rated voltage:380V Rated frequency:50HZ Phase :Three Pole:Four Rated power:18.5Kw(25HP) No load speed:1470RPM Power factor:0.86 Work duty:S1 Protection class:IP44 Insulation class:B Copper wire motor Packed by wood box	1207.50
EMY180L-4		Three phase asynchronous motor	Rated voltage:380V Rated frequency:50HZ Phase :Three Pole:Four Rated power:22Kw(30HP) No load speed:1470RPM Power factor:0.86 Work duty:S1 Protection class:IP44 Insulation class:B Copper wire motor Packed by wood box	1386.00
FHOGD-37F		Air Compressor	Rated power- 37kw 2950r/min 3 phase Smart logic Panel Starting Air Outlet Diameter- 1 1/4" Free Air Delivery-6.6 / 240cfm 7 Bar	12337.50
FHOGY50A-H		Air Compressor- Diesel	Rated power- 40kw (50HP) Free Air Delivery 4.6 / 165cfm 3000r/min Smart logic Panel Starting Air Outlet Diameter- 2-3/4" 7Bar	17850.00